

## PS-6120 FP 6 Volt 12.0 AH

### Rechargeable Sealed Lead Acid Battery



We've Got The Power.™




### Features

- Absorbent Glass Mat (AGM) technology for superior performance
- Valve regulated, spill proof construction allows safe operation in any position
- Power/volume ratio yielding unrivaled energy density
- Rugged impact resistant ABS case and cover (UL94-HB)
- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified
- U.L. recognized under file number MH 20845


### Terminals

(mm)

- FP - FASTON Polarized  
Positive: F2 - Quick disconnect tabs, 0.250" x 0.032" - Mate with AMP. INC. FASTON "250" series  
Negative: F1 - Quick disconnect tabs, 0.187" x 0.032" - Mate with AMP. INC. FASTON "187" series



### Physical Dimensions: in (mm)



L: 4.25 (108) W: 2.80 (71) H: 5.55 (141) HT: 5.55 (141)

Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.

### Performance Specifications

**Nominal Voltage** ..... 6 volts (3 cells)

#### Nominal Capacity

20-hr. (600mA to 5.25 volts) .....	12.00 AH
10-hr. (1.19A to 5.25 volts) .....	11.90 AH
5-hr. (2.21A to 5.10 volts) .....	11.05 AH
1-hr. (8A to 4.50 volts) .....	8.00 AH
15-min. (25.5A to 4.50 volts).....	6.38 AH

**Approximate Weight** ..... 4.80 lbs. (2.18 kg)

**Energy Density** (20-hr. rate) ..... 1.09 W-h/in<sup>3</sup> (66.53 W-h/l)

**Specific Energy** (20-hr. rate) ..... 15.00 W-h/lb (33.07 W-h/kg)

**Internal Resistance** (approx.) ..... 12 milliohms

**Max Discharge Current** (7 Min.) ..... 36.0 amperes

**Max Short-Duration Discharge Current** (10 Sec.)..... 120.0 amperes

#### Shelf Life (% of nominal capacity at 68°F (20°C))

1 Month .....	97%
3 Months.....	91%
6 Months .....	83%


#### Operating Temperature Range

Charge.. .....	-4°F (-20°C) to 122°F (50°C)
Discharge.....	-40°F (-40°C) to 140°F (60°C)


**Case** ..... ABS Plastic

**Power-Sonic Chargers** .....PSC-61000A, 61000A-C


### Shelf Life & Storage




### Discharge Characteristics




### Discharge Time vs. Discharge Current



### Life Characteristics in Stand-By Use



### Life Characteristics in Cyclic Use



### Charging

**Cycle Applications:** Limit initial current to 3.6A. Charge until battery voltage (under charge) reaches 7.20 to 7.35 volts at 68°F (20°C). Hold at 7.20 to 7.35 volts until current drops to under 120mA. Battery is fully charged under these conditions, and charger should be disconnected or switched to “float” voltage.

**“Float” or “Stand-By” Service:** Hold battery across constant voltage source of 6.75 to 6.90 volts continuously. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition.

**Note:** Due to the self-discharge characteristics of this type of battery, it is imperative that they be charged within 6 months of storage, otherwise permanent loss of capacity might occur as a result of sulfation.

### Chargers

Power-Sonic offers a wide range of chargers suitable for batteries up to 100AH. Please refer to the Charger Selection Guide in our specification sheets for “C-Series Switch Mode Chargers” and “Transformer Type A and F Series”. Please contact our Technical department for advice if you have difficulty in locating suitable models.

### Further Information

Please refer to our website [www.power-sonic.com](http://www.power-sonic.com) for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc..

### Contact Information

[www.power-sonic.com](http://www.power-sonic.com)

#### DOMESTIC SALES

Tel: +1-619-661-2020  
Fax: +1-619-661-3650  
national-sales@power-sonic.com

#### CUSTOMER SERVICE

Tel: +1-619-661-2030  
Fax: +1-619-661-3648  
customer-service@power-sonic.com

#### TECHNICAL SUPPORT

Tel: +1-619-661-2020  
Fax: +1-619-661-3648  
support@power-sonic.com

#### INTERNATIONAL SALES

Tel: +1-650-364-5001  
Fax: +1-650-366-3662  
battery@power-sonic.com